

C326C682K1R5TA7301

GoldMax 300 Comm X7R, Ceramic, 6800 pF, 10%, 100 VDC, X7R, GoldMax, Commercial Standard, Lead Spacing = 2.54mm

Click [here](#) for the 3D model.

Dimensions

L 5.08mm MAX
H 7.62mm MAX
T 3.18mm MAX
S 2.54mm +/-0.78mm
H0 16mm +/-0.5mm
F 0.51mm +0.1/-0.025mm
E 5.08mm NOM

Packaging Specifications

Packaging T&R, 305mm
Packaging Quantity 2500

General Information

Series GoldMax 300 Comm X7R
Style Radial
Description GoldMax, Commercial Standard
RoHS Yes
Termination Tin
Failure Rate N/A
AEC-Q200 No
Halogen Free Yes

Specifications

Capacitance	6800 pF
Measurement Condition	1 kHz 1.0Vrms
Capacitance Tolerance	10%
Voltage DC	100 VDC
Dielectric Withstanding Voltage	250 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	X7R
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	0.15, 1kHz 1.0Vrms
Dissipation Factor	2.5% 1 kHz 1.0Vrms
Aging Rate	3% Loss/Decade Hour
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.