

Features





- Single module with standard shielded RJ45 plug and jack
- The RJ45 inserts are protected by a reliable plastic insulator
- 360° shielded contact
- Field assembly without tools possible by means of *HARAX*® rapid termination in IDC technology
- Suitable for termination of massive and flexible wires

Technical characteristics

| | |
|---|------------------------------------|
| Number of contacts | 4 |
| Insulation resistance | $>10^{10} \Omega$ |
| Limiting temperature | -40 ... +70 °C |
| Mating cycles | ≥ 500 |
| Wire outer diameter | $\leq 1.6 \text{ mm}$ |
| Transmission characteristics | Cat. 5, Class D up to 100 MHz |
| Data rate | 10 Mbit/s, 100 Mbit/s |
| Material (insert) | Polycarbonate (PC), Polyamide (PA) |
| Colour (insert) | RAL 7032 (pebble grey) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |

Specifications and approvals

EN 60664-1
IEC 61984
DNV GL
IEC 60603-7
DIN EN 45545-2 R26: HL1, HL2, HL3

| Identification | | Part number Male | Drawing (dimensions in mm) |
|--|-----------------------------|----------------------------------|--|
| Han-Modular®, Han® RJ45 module, Single module  | | 09 14 001 4623 |  |
| Data connectors, RJ Industrial RJ45 connector set, Shielded  | AWG 24 ... AWG 22 AWG 26 | 09 45 400 1100 09 45 400 1109 |  <p>Wire outer diameter $\leq 1.6 \text{ mm}$</p> |