



EXC

Two-Way Radio Antenna

Today's work and lifestyles require us to communicate anytime, anywhere whether on the move or sitting still. Bluetooth and 802.11 standards make wireless connections to computer networks and other devices possible, while at the same time enabling freedom of movement.

Laird Connectivity's practical and rugged external wireless device antennas are designed to fit into the portable devices used in office, industrial and home environments. The antennas feature flexible elements and many are ½ wave coaxial dipole design for reduced ground dependence and improved performance.

FEATURES AND BENEFITS

- Injection-molded ¼ wave flexible cable antenna
- High durability, high efficiency
- Textured finish with strain-relief base
- Available in various standard connectors
- An original Tuf Duck antenna

APPLICATIONS

- For Bluetooth and IEEE 802.11b/g devices

SPECIFICATIONS	
Model Name	EXCxxx
Operating Frequency (MHz)	UHF Trunking/Cellular
VSWR - Max	1.5:1
Nominal Impedance (Ohms)	50
Power Handling (W)	50
Polarization	Vertical
Ingress Protection Rating	IP67
Drop Test (M)	1
Operating Temperature - °C (°F)	-40 to +85°C (-40 to +185°F)

CONFIGURATION

PART NUMBER	FREQUENCY BAND	CONNECTOR	AVERAGE LENGTH
EXC340	336-343 MHz	BNX	20.32 cm (8.0 in.)
EXC400	400-420 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMV, TN, TNX	17.15 - 17.8 cm (6.75 - 7.0 in.)
EXC410		SMI	
EXC420	420-450 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN, TNX	17.15 - 17.8 cm (6.75 - 7.0 in.)
EXC450	450-470 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMV, TN, TNX	16.23 - 17.53 cm (6.39 - 6.9 in.)
EXC470	470-512 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMV, TN, TNX	15.57 - 17.02 cm (6.13 - 6.7 in.)
EXC806	806-866 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN, TNX	9.4 - 11.68 cm (3.7 - 4.6 in.)
EXC868		SM	8.9 cm (3.5 in.)
EXC902	902-960 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN, TNX	8.9 - 9.27 cm (3.5 - 3.65 in.)
EXC1000	1000 MHz	BN	8.38 (3.3 in.)

Note: Order by antenna model, frequency, and connector (for example: EXC450MX). The length of each antenna varies according to the chosen connector.

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, and TE connectivity (logo) are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warranted to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

08/22 Original