

R60PI3220GY40J

Aliases (60PI3220GY40J)

R60, Film, Metallized Polyester, Automotive Grade, 0.22 uF, 5%, 630 VDC, 85°C, Lead Spacing = 15mm



Click [here](#) for the 3D model.

Dimensions

| | |
|----|-----------------|
| L | 18mm +0.5mm |
| H | 14.5mm +0.1mm |
| T | 8.5mm +0.2mm |
| S | 15mm +/-0.4mm |
| H0 | 18.5mm +/-0.5mm |
| F | 0.8mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|------------|
| Packaging | T&R, 355mm |
| Packaging Quantity | 300 |

General Information

| | |
|----------------|---|
| Series | R60 |
| Dielectric | Metallized Polyester |
| Style | Radial |
| Features | Automotive Grade, DC Multipurpose Applications |
| RoHS | Yes |
| Lead | Wire Leads |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |
| Miscellaneous | Upper Operating Temperature Of 125C Is Allowed For A Maximum Operating Time Of 1,000 Hours. Above 85C, DC And AC Voltage Derating Is 1.25%/C. |

Specifications

| | |
|-----------------------|------------|
| Capacitance | 0.22 uF |
| Capacitance Tolerance | 5% |
| Voltage AC | 220 VAC |
| Voltage DC | 630 VDC |
| Temperature Range | -55/+105°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 1% 1kHz |
| Insulation Resistance | 30 GOhms |
| Max dV/dt | 25 V/us |
| Inductance | 10 nH |