

# Product data sheet

## Characteristics

# SSP03XDSE15A

Surge protection device, XDSE, 150kA,  
240/120 VAC HLD, 3 phase, 4 wire, SPD type  
2



### Main

Product	Surge protection device
---------	-------------------------

### Complementary

Surge Current	150 A per phase
Voltage Rating	240/120 V HLD AC
Number of Phases	3 phase
Wiring Configuration	4-wire
MCOV	150 V 320 V
Rated Current	20 kA
Input voltage	700 V L-N 1200 V L-N 700 V L - G 1200 V L - G 600 V L - L 1000 V N - G 2000 V N - G
Height	5.98 in (152 mm)
Width	5.98 in (152 mm)
Depth	3.98 in (101 mm)

### Environment

Enclosure Rating	NEMA 4X
------------------	---------

### Ordering and shipping details

Category	08466-SURGE PROTECTION HWA
Discount Schedule	DE1B
Nbr. of units in pkg.	1
Package weight(Lbs)	3.98 lb(US) (1.805 kg)
Returnability	No

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.98 in (15.2 cm)
Package 1 width	5.98 in (15.2 cm)
Package 1 Length	3.98 in (10.1 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>