

# Housing - HC-STA-D15-SLWSC-2SSP21-EL-AL - 1424373

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Box mounting bases D15, with single locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PA, cable outlets: 2, lateral, height: 52 mm, cable gland: none, support sleeve: no, 2x Pg21, protective cover: yes, Standard



## **Key Commercial Data**

Packing unit	1 pc
GTIN	4 055626 371139
GTIN	4055626371139

### Technical data

#### **Dimensions**

Height	52 mm
Width	51 mm
Length	80 mm

### Ambient conditions

Degree of protection (IP)	IP66 (with locked protective cover)	
	IP67 (when plugged in)	
Ambient temperature (operation)	-40 °C 125 °C	

#### General

Size	D15	
Housing type	Box mounting bases	
Color	gray aluminum	
Locking type	with single locking latch	
No. of cable outlets	2 lateral	
Cable outlet		
Screw connection	none	
Type of the screw connection	2x Pg21	
Protective cover	yes	



# Housing - HC-STA-D15-SLWSC-2SSP21-EL-AL - 1424373

### Technical data

### General

Housing material	Die-cast aluminum, salt water resistant	
Housing surface material	uncoated	
Material lock	PA	
Material, protective cover	PA	
Assembly instructions	One opening is sealed with a plastic filler plug and can be opened using a screwdriver.	

### **Environmental Product Compliance**

China RoHS	Environmentally Friendly Use Period = 50	
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"	

## **Approvals**

Approval	s
----------	---

Approvals

EAC / DNV GL

Ex Approvals

### Approval details

	EAC	ERC	EAC-Zulassung
--	-----	-----	---------------

DNV GL	<u>v</u>	https://approvalfinder.dnvgl.com/	TAE000037S

Phoenix Contact 2019 @ - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Fax +49 5235 3 41200

http://www.phoenixcontact.com