



Product: <u>5100FE</u> ☑

Security & Sound, 2 Conductor 14 AWG, BC, Shielded, CL3R, FPLR

# **Product Description**

Security & Commercial Audio Cable, Riser-CL3R-FPLR, 2-14 AWG stranded bare copper conductors with polypropylene insulation, Beldfoil® shield and PVC jacket with ripcord

# **Technical Specifications**

### **Product Overview**

Suitable Applications:	Intercom/PA Systems, Sound/Audio Systems, Fire Alarm Systems

## **Construction Details**

#### Conductor

Element	Number of Element	Size	Stranding	Material
Conductor(s)	2	14 AWG	19x26	BC - Bare Copper

#### Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	PP - Polypropylene	0.011 in (0.28 mm)	0.092 in (2.3 mm)	Black, White

### Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Tape	Bi-Laminate (Alum+Poly)	100%	22 AWG (7x30) TC

### **Outer Jacket**

	Material	Nom. Thickness	Nom. Diameter	Ripcord
	PVC - Polyvinyl Chloride	0.017 in (0.43 mm)	0.222 in (5.64 mm)	Yes
Ī	Overall Cable Diameter (I	Nominal): 0.222 in (	5.64 mm)	

### Overall Gazio Biameter (verillia).

# Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	2.54 Ohm/1000ft	54 pF/ft (180 pF/m)	97.25 pF/ft (319.1 pF/m)	25 Amps per conductor @ 30°C

# Voltage

UL Voltage Rating 300 V (CL3R, FPLR)

# **Mechanical Characteristics**

**Electrical Characteristics** 

## Temperature

UL Temperature	Operating
75°C	-20°C to +75°C

### Bend Radius

Stationary Min.	Installation Min.
2.2 in (56 mm)	2.2 in (56 mm)

Max. Pull Tension:	104.1 lbs (47.22 kg)
Bulk Cable Weight:	37 lbs/1000ft

### **Standards and Compliance**

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Reaction to Fire:	UL 1666 Riser, IEEE 1202 FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 725, Article 760, CL3R, FPLR
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6100FH

### History

Update and Revision:	Revision Number: 0.527 Revision Date: 04-14-2023	

### **Part Numbers**

#### Variants

Item #	Color	Putup Type	Length	UPC/EAN
5100FE.00152	Chrome	Reel	152 m	8719605007704
5100FE.00305	Chrome	Reel	305 m	8719605007728
5100FE.001000	Chrome	Reel	1,000 m	8719605007698
5100FE 008500	Gray	Reel	500 ft	612825156222
5100FE 0081000	Gray	Reel	1,000 ft	612825156246
5100FE 008U1000	Gray	UnReel	1,000 ft	612825423591
5100FE 008Z1000	Gray	ReelTuff Box	1,000 ft	612825156260
5100FE.003000	Gray	Reel	3,000 m	8719605007711
5100FE 0021000	Red	Reel	1,000 ft	612825423584
5100FE 002Z1000	Red	ReelTuff Box	1,000 ft	612825156239

## © 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.