



## A-BASE ANTENNAS

### VHF/UHF/700-800 MHz/2400 MHz

Laird Connectivity's ongoing commitment to refinement in mechanical and electrical design has resulted in the most technically advanced mobile antennas on the market. Exclusive features such as stainless-steel whips, housings constructed with ABS material injected molded around a solid brass insert, and gold-plated push pin contacts make Laird the obvious choice for quality and long-lasting value for demanding mobile radio communications.

### FEATURES AND BENEFITS

- All featuring NMO mounts for rapid deployment and reliable performance
- Exclusive Laird Connectivity gold-plated push-pin contact provides the most corrosion resistance and power transfer over time
- Long tuning ferrule allows for greater freedom in frequency adjustment without trimming
- Stainless-steel corona ball stays on the rod; no dissimilar metal interaction associated with competitor designs

MODEL	FREQUENCY	COLOR	GAIN	RADIATOR	BASE
<b>VHF Models</b>					
AFT	118-896 MHz Field Tunable	Chrome	Unity	0.100-inch diameter ¼ wave	Solid
ABFT	118-896 MHz Field Tunable	Black	Unity	0.100-inch diameter ¼ wave	Solid
A150	150-174 MHz	Chrome	Unity	0.100-inch diameter ¼ wave	Solid
A150S	150-174 MHz	Chrome	Unity	0.100-inch diameter ¼ wave	Spring
AB150	150-174 MHz	Black	Unity	0.100-inch diameter ¼ wave	Spring
<b>UHF Models</b>					
A450	450-470 MHz	Chrome	Unity	0.100-inch diameter ¼ wave	Solid
AB450	450-470 MHz	Black	Unity	0.100-inch diameter ¼ wave	Solid
A4503	450-470 MHz	Chrome	3.5 dBi	Open Collinear	Solid
A4503C	450-470 MHz	Chrome	3.5 dBi	Closed Collinear	Solid
AB4503	450-470 MHz	Black	3.5 dBi	Open Collinear	Solid
AB4503C	450-470 MHz	Black	3.5 dBi	Closed Collinear	Solid

MODEL	FREQUENCY	COLOR	GAIN	RADIATOR	BASE
<b>700-800 MHz Antennas</b>					
A7603	760-870 MHz	Chrome	3 dBi	Open Collinear	Solid
AB7603	760-870 MHz	Black	3 dBi	Open Collinear	Solid
A8063	806-896 MHz	Chrome	3 dBi	Open Collinear	Solid
A8963	896-970 MHz	Chrome	3 dBi	Open Collinear	Solid
A8063C	806-896 MHz	Chrome	3.5 dBi	Closed Collinear	Solid
A8065CT	806-896 MHz	Chrome	5 dBi	Closed Trilinear	Solid
AB8065CT	806-896 MHz	Black	5 dBi	Closed Trilinear	Solid
AB8063	806-896 MHz	Black	3 dBi	Open Collinear	Solid
AB8963	896-970 MHz	Black	3 dBi	Open Collinear	Solid
AB8063C	806-896 MHz	Black	3.5 dBi	Closed Collinear	Solid
<b>800 MHz Models with Spring</b>					
A8063S	806-896 MHz	Chrome	3 dBi	Open Collinear	Spring
A8063CS	806-896 MHz	Chrome	3.5 dBi	Closed Collinear	Spring
A8065CTS	806-896 MHz	Chrome	5 dBi	Closed Trilinear	Spring
AB8063S	806-896 MHz	Black	3 dBi	Open Collinear	Spring
AB8063CS	806-896 MHz	Black	3.5 dBi	Closed Collinear	Spring
AB8065CTS	806-896 MHz	Black	5 dBi	Closed Trilinear	Spring
<b>2.4 GHz Models</b>					
A2400	2400-2500 MHz	Chrome	Unity	0.100-inch diameter ¼ wave	Solid
AB2400	2400-2500 MHz	Black	Unity	0.100-inch diameter ¼ wave	Solid
A24003-OC	2400-2500 MHz	Chrome	3 dBi	Open Collinear	Solid
AB24003-OC	2400-2500 MHz	Black	3 dBi	Open Collinear	Solid
A24005-OT	2400-2500 MHz	Chrome	5 dBi	Open Collinear	Solid
AB24005-OT	2400-2500 MHz	Black	5 dBi	Open Collinear	Solid

MODEL	FREQUENCY	COLOR	GAIN	RADIATOR	BASE
<b>Multi-Band Models</b>					
A144/440C	144-148 MHz/440-450 MHz	Chrome	Unity	Closed Collinear	Solid
AB144/440C	144-148 MHz/440-450 MHz	Black	Unity	Closed Collinear	Solid
A150/450C	150-174 MHz/450-470 MHz	Chrome	Unity	Closed Collinear	Solid
A150/450CS	150-174 MHz/450-470 MHz	Chrome	Unity	Closed Collinear	Spring
AB150/450C	150-174 MHz/450-470 MHz	Black	Unity	Closed Collinear	Solid
AB150/450CS	150-174 MHz/450-470 MHz	Black	Unity	Closed Collinear	Spring
ABSCANC	150-174 MHz/450-470 MHz/	Black	Unity	Closed Collinear	Solid
ABSCANCS	150-174 MHz/450-470 MHz/760-960 MHz	Black	Unity	Closed Collinear	Spring

## TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

## te.com

TE, and TE connectivity (logo) are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warranted to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

08/22 Original