



# DC FAN LIFE EXPERIMENT REPORT

Available for these models with lower speed and same physical structure. All model may be followed by Rx or Fxx series suffixes. This test report applies to **FFB127x127x38 mm** series as the right table

FFB1312EHE	FFB1312SHE	FFB1312VHE	FFB1312HHE	FFB1312HE
FFB1312ME	FFB1312LE	FFB1324EHE	FFB1324SHE	FFB1324VHE
FFB1324HHE	FFB1324HE	FFB1324ME	FFB1324LE	

**Representative Test P/N : FFB1312EHE-F00**

**Equipment: 1.Oven: E24-F0031**

On/Off Cycles: Every 500 hours

**◎ L<sub>10</sub> Expectancy: 70,000 hours minimum @ fan rated voltage and the temperature of 40°C**

According to the equation for **Weibull distribution**,  $MTTF \doteq 7 \times L_{10} = 490,000$  hours

And we rely on a zero failure Weibull test strategy and accelerated testing technique, to determine the total test time (t) for verifying the above life estimation by the equations,

$$t = 1.036 \times MTTF \times [(B_{r;c}) \div n]^{0.91} \div A_F, \text{ and } A_F = 2^{(T_s - T_u)/10}$$

where, ( $B_{r;c}$ ) is Poisson distribution factor with the failure number of r equal to 0 and

the decimal confidence level of c equal to 0.90(90%), and

Stress/Elevated Temperature Ts (°C)	Unstress Temperature Tu (°C)	Acceleration Factor A <sub>F</sub>	Quantity of Test Devices n (pcs)	Poisson Distribution Factor B <sub>r;c</sub>	Required test time with zero failure t (hours)	Actual test time with zero failure t (hours)	Verified MTTF 40 °C (hours)	Verified L <sub>10</sub> 40 °C (hours)
70	40	8.00	56	2.303	3,478	3,478.0	490,031	70,004

## Test Progress:

Date for Test Beginning	Date for Test Termination (at least)	Current Test Status		Current Total Test Time (hours)
2004/1/13 10:30 AM	2004/8/24 8:46 PM	<input type="checkbox"/> In process	<input type="checkbox"/> In process (exceed requested)	<input checked="" type="checkbox"/> Termination 3478.0

Herewith , we could assume as right on the basis of above test result. Besides, if the actual test time exceed the required, it comes out that those fans' L<sub>10</sub> expectancy and MTTF are greater than the warrant. ( **MTTF** : means Mean Time To Failures, it should be used in a non-repairable system setting. Now we show the MTTF in our life report, that's because we will not repair the failed fans during life experiment. **MTBF**: means Mean Time Between failures, it should be used in a repairable system setting. **Basically , MTBF is equal to MTTF , they use same formula to work out a life data.** )

Temperature for MTTF Estimation (°C)	Acceleration Factor A <sub>F</sub>	Estimated MTTF (hours)	Estimated L <sub>10</sub> (hours)
25	22.63	1,386,017	198,002
30	16.00	980,062	140,009
40	8.00	490,031	70,004
50	4.00	245,015	35,002
60	2.00	122,508	17,501
70	1.00	61,254	8,751

## Test Result

- Accept  
 Reject

QE File No.	Time-out for function test or others (hours)	Issued Date	Reported By	Approved By
DG04FNL002	1908.50	2004/8/24 9:00 PM	Huiling.Fu	Even.Liu

Note: The test sample equivalent to STD, Part number: FFB1312EHE-F00 .



# DC FAN FUNCTION TEST RECORD

## FOR LIFE EXPERIMENT

Available for these models with lower speed and same physical structure. All model may be followed by Rx or Fxx series suffixes. This test report applies to FFB127x127x38 mm series as the right table				FFB1312EHE	FFB1312SHE	FFB1312VHE	FFB1312HHE	FFB1312HE					
				FFB1312ME	FFB1312LE	FFB1324EHE	FFB1324SHE	FFB1324VHE					
				FFB1324HHE	FFB1324HE	FFB1324ME	FFB1324LE						
<b>Required Test Time (hrs)</b>		<b>Date for Test Beginning</b>		<b>Date for Test Termination</b>		<b>Sample Size (pcs):</b>	<b>Failure (pcs):</b>	<b>Current Total Test Time (hrs)</b>					
3,478		2004/1/13 10:30 AM		2004/8/24 8:46 PM		56	0	<b>3478.0</b>					
Representative Test P/N :FFB1312EHE-F00				<b>Current Test Status</b>		<input type="checkbox"/> In process	<input type="checkbox"/> In process (exceed requested)	<input checked="" type="checkbox"/> Termination					
Equipment: 1.Oven: E24-F0031						On/Off Cycles: Every 500 hours							
<b>Test Data Between Initial Test and Final Test</b>													
Sample No.	Initial Test	Final Test	Deviation (%)	Initial Test	Final Test	Deviation (%)	Initial Test	Final Test	Deviation (%)				
	Current Spec. (A)	Current Spec. (A)		Speed Spec. (RPM)	Speed Spec. (RPM)		Noise Spec. (dB A)	Noise Spec. (dB A)					
4.11Max.	4.11Max.	3542-4158	3542-4158	63.5Max	63.5Max								
1	2.22	2.24	0.9	3945	3990	1.1	60.6	60.3	-0.5				
2	2.16	2.14	-0.9	3903	3969	1.7	59.8	59.5	-0.5				
3	2.17	2.31	6.5	3960	3939	-0.5	60.6	60.1	-0.8				
4	2.08	2.11	1.4	3863	3909	1.2	60.1	59.6	-0.8				
5	2.14	2.19	2.3	3893	3939	1.2	60.3	60.0	-0.5				
6	2.10	2.24	2.3	3874	3956	2.1	59.5	59.6	0.2				
7	2.19	2.24	4.2	3974	3954	-0.5	59.9	59.8	-0.2				
8	2.15	2.27	4.1	3896	3950	1.4	60.4	60.0	-0.7				
9	2.18	2.18	0.9	3948	3944	-0.1	60.0	59.9	-0.2				
10	2.16	2.17	-2.3	3863	3873	0.3	60.6	60.2	-0.7				
11	2.22	2.19	3.3	3889	3941	1.3	60.0	59.7	-0.5				
12	2.12	2.22	1.4	3840	3927	2.3	60.2	59.8	-0.7				
13	2.19	2.19	0.5	3933	3943	0.3	60.5	60.1	-0.7				
14	2.18	2.22	1.8	3924	3944	0.5	59.2	59.5	0.5				
15	2.18	2.14	-1.4	3909	3990	2.1	60.2	60.0	-0.3				
16	2.17	2.25	1.8	3862	3947	2.2	59.6	59.8	0.3				
17	2.21	2.29	5.5	3960	3981	0.5	60.5	60.6	0.2				
18	2.17	2.12	-0.9	3869	3966	2.5	60.3	60.5	0.3				
19	2.14	2.22	2.8	3914	3910	-0.1	60.2	60.1	-0.2				
20	2.16	2.28	6.5	3908	3962	1.4	59.6	59.8	0.3				
21	2.14	2.19	2.3	3886	3972	2.2	60.5	60.1	-0.7				
22	2.19	2.05	-6.4	3884	3982	2.5	60.1	60.0	-0.2				
23	2.28	2.27	-0.4	3890	3922	0.8	59.2	59.6	0.7				
24	2.14	2.23	4.2	3909	4005	2.5	60.0	59.5	-0.8				
25	2.13	2.21	3.8	3906	3937	0.8	60.3	60.0	-0.5				
26	2.17	2.20	1.4	3950	3927	-0.6	60.1	60.3	0.3				
27	2.24	2.24	0.0	3886	3899	0.3	60.5	60.2	-0.5				
28	2.11	2.19	3.8	3966	3897	-1.7	60.1	60.6	0.8				
29	2.16	2.22	2.8	3897	3979	2.1	59.9	60.0	0.2				
30	2.22	2.15	-3.2	3894	4032	3.5	60.5	59.9	-1.0				
31	2.12	2.19	3.3	3921	3948	0.7	60.4	60.1	-0.5				
32	2.13	2.20	3.3	3878	3928	1.3	60.2	60.2	0.0				
33	2.10	2.15	2.4	3873	3911	1.0	59.4	60.0	1.0				
34	2.13	2.18	2.3	3942	3896	-1.2	59.9	59.7	-0.3				
35	2.19	2.15	-1.8	3899	3929	0.8	60.5	60.1	-0.7				
<b>QE File No.</b>		<b>Time-out for function test or others (hours)</b>		<b>Issued Date</b>		<b>Reported By</b>		<b>Approved By</b>					
<b>DG04FNL002</b>		<b>1908.50</b>		<b>2004/8/24 9:00 PM</b>		<b>Huiling.Fu</b>		<b>Even.Liu</b>					



# DC FAN FUNCTION TEST RECORD

## FOR LIFE EXPERIMENT

Available for these models with lower speed and same physical structure. All model may be followed by Rx or Fxx series suffixes. This test report applies to FFB127x127x38 mm series as the right table				FFB1312EHE	FFB1312SHE	FFB1312VHE	FFB1312HHE	FFB1312HE	
				FFB1312ME	FFB1312LE	FFB1324EHE	FFB1324SHE	FFB1324VHE	
				FFB1324HHE	FFB1324HE	FFB1324ME	FFB1324LE		
Required Test Time (hrs)	Date for Test Beginning	Date for Test Termination	Sample Size (pcs):	Failure (pcs):	Current Total Test Time (hrs)				
3,478	2004/1/13 10:30 AM	2004/8/24 8:46 PM	56	0	<b>3478.0</b>				
Representative Test P/N :FFB1312EHE-F00				Current Test Status	<input type="checkbox"/> In process	<input type="checkbox"/> In process (exceed requested)	<input checked="" type="checkbox"/> Termination		
Equipment: 1.Oven: E24-F0031				On/Off Cycles: Every 500 hours					
Test Data Between Initial Test and Final Test									
Sample No.	Initial Test	Final Test	Deviation (%)	Initial Test	Final Test	Deviation (%)	Initial Test	Final Test	Deviation (%)
	Current Spec. ( A )	Current Spec. ( A )		Speed Spec. ( RPM )	Speed Spec. ( RPM )		Noise Spec. ( dB A )	Noise Spec. ( dB A )	
	<b>4.11Max.</b>	<b>4.11Max.</b>		<b>3542-4158</b>	<b>3542-4158</b>		<b>63.5Max</b>	<b>63.5Max</b>	
36	2.15	2.18	1.4	3840	3857	0.4	59.7	59.5	-0.3
37	2.14	2.09	-2.3	3891	3907	0.4	60.0	59.8	-0.3
38	2.18	2.24	2.8	3943	3901	-1.1	60.5	60.2	-0.5
39	2.16	2.22	2.8	3904	3998	2.4	59.2	60.2	1.7
40	2.19	2.21	0.9	3921	3909	-0.3	60.8	60.3	-0.8
41	2.18	2.23	2.3	3863	3844	-0.5	60.0	60.2	0.3
42	2.17	2.13	-1.8	3843	3898	1.4	60.4	60.6	0.3
43	2.20	2.27	3.2	3922	3859	-1.6	60.6	60.5	-0.2
44	2.19	2.16	-1.4	3846	3916	1.8	60.7	60.4	-0.5
45	2.16	2.18	0.9	3886	3928	1.1	59.8	60.0	0.3
46	2.14	2.09	-2.3	3862	3932	1.8	59.8	59.7	-0.2
47	2.15	2.25	4.7	3856	3964	2.8	60.3	60.5	0.3
48	2.24	2.25	0.4	3918	4005	2.2	59.7	59.6	-0.2
49	2.22	2.32	4.5	3933	3907	-0.7	60.5	60.2	-0.5
50	2.25	2.25	0.0	3862	3960	2.5	60.8	60.5	-0.5
51	2.28	2.29	0.4	3936	3929	-0.2	60.5	60.2	-0.5
52	2.19	2.17	-0.9	3968	4004	0.9	60.7	60.3	-0.7
53	2.22	2.30	3.6	3909	3961	1.3	60.3	60.1	-0.3
54	2.24	2.25	0.4	3895	3902	0.2	59.2	59.8	1.0
55	2.24	2.29	2.2	3909	3878	-0.8	60.4	59.8	-1.0
56	2.30	2.31	0.4	3940	3924	-0.4	60.3	60.1	-0.3
X-Bar	2.177	2.209	-	3901.9	3937.3	-	60.14	60.03	-
	0.047	0.060	-	34.762	40.384	-	0.427	0.306	-
QE File No.	Time-out for function test or others (hrs)		Issued Date		Reported By		Approved By		
DG04FNL002	1908.50		2004/8/24 9:00 PM		Huiling.Fu		Even.Liu		