

R533R418040P0K

Aliases (533R418040P0K)

R53 X2 310 VAC, Film, Metallized Polypropylene, Automotive Safety, 1.8 uF, 10%, 310 VAC (X2), 630 VDC, 110°C, Lead Spacing = 27.5mm



Click here for the 3D model.

Dimensions	
L	32mm +0.5/-0.7mm
н	20mm +0.3/-0.7mm
т	11mm +0.3/-0.7mm
S	27.5mm +/-0.4mm
LL	30mm +5mm
F	0.8mm +/-0.05mm

Packaging Specifications

Packaging Quantity

336

General Information		
Series	R53 X2 310 VAC	
Dielectric	Metallized Polypropylene	
Style	Radial	
Features	Automotive Grade, EMI Safety	
RoHS	Yes	
Lead	Wire Leads	
Safety Class	X2	
Qualifications	ENEC, UL, cUL, CQC, AEC-Q200	
AEC-Q200	Yes	
THB Performance	Yes	
Component Weight	8.8 g	

Specifications			
Capacitance	1.8 uF		
Capacitance Tolerance	10%		
Voltage AC	310 VAC (X2)		
Voltage DC	630 VDC		
Temperature Range	-40/+110°C		
Rated Temperature	110°C		
Dissipation Factor	0.2% 1kHz		
Insulation Resistance	16.6667 GOhms		
Max dV/dt	150 V/us		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.