

## Micro USB to USB OTG Host Adapter Cable, 5-Pin Micro USB B to USB A M/F, 6-in.

MODEL NUMBER: **U052-06N**



Connect a USB OTG ready Tablet or Smartphone to USB 2.0 Devices

### Description

Tripp Lite U052-06N, USB OTG Adapter, is the perfect solution for expanding the capabilities of an OTG enabled SmartPhone, Tablet, or other OTG devices, by directly connecting to USB peripherals, such as a USB thumb drive or a USB keyboard and mouse. Add a USB hub to the adapter to create additional ports to connect multiple USB devices. USB OTG technology makes this connection easy, and does not require drivers or software...Plug-n-Play! Connect the adapter to the Micro-B port on an OTG enabled mobile device, and then connect the USB device directly to the USB A port on the adapter for immediate use.

### Features

- Micro USB Male to standard USB "A" Female On-The-Go ( OTG ) adapter
- Plug-n-Play...No Drivers or Software required
- Connect one USB device, or add a multi-port hub for multiple USB device connections
- 6inch length allows for flexible access for attached peripherals

## Specifications

OVERVIEW	
UPC Code	037332184375
INPUT	
Cable Length (ft.)	0.5
Cable Length (m)	0.2

### Highlights

- Connect Thumb Drives, Keyboards, etc to OTG Tablets and Phones
- Plug-n-Play...No Software or Drivers Required

### System Requirements

- USB OTG enabled Tablet, SmartPhone, or other OTG mobile device

### Package Includes

- U052-06N USB OTG Adapter



Cable Length (in.)	6
Cable Length (cm)	15.24
<b>PHYSICAL</b>	
Cable Jacket Rating	VW-1
Cable Outer Diameter (OD)	4.5MM
Color	Black
Material of Construction	PVC
Shipping Dimensions (hwd / cm)	17.78 x 7.62 x 1.27
Shipping Dimensions (hwd / in.)	7.00 x 3.00 x 0.50
Shipping Weight (kg)	0.02
Shipping Weight (lbs.)	0.04
Wire Gauge (AWG)	28/24
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	14 to 140 F (-10 to 60 C)
Storage Temperature Range	-4 to 185 F (-20 to 85 C)
Relative Humidity	10% to 85%, Non-Condensing
<b>CONNECTIONS</b>	
Side A - Connector 1	USB A (FEMALE)
Side B - Connector 1	MICRO-USB B (MALE)
Connector Plating	Nickel
Contact Plating	Gold
<b>FEATURES &amp; SPECIFICATIONS</b>	
USB Specification	USB 2.0 (up to 480 Mbps)
Technology	USB 2.0 (High Speed); USB
<b>CERTIFICATIONS</b>	
Certifications	Tested to CE, FCC, RoHS, REACH
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

<https://www.tripplite.com/products/product-certification-agencies>