




HV RAD-LDD Indust X7R HV, Ceramic, 1000 pF, 10%, 10000 VDC, X7R, Commercial, High Voltage, Lead Spacing = 29.84mm



Click here for the 3D model.

Dimensions	
L	31.75mm MAX
Н	15.24mm MAX
Т	6.89mm MAX
S	29.84mm +/-0.76mm
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm

Packaging Specifications

Packaging	Bulk, Bag
Packaging Quantity	1

on
HV RAD-LDD Indust X7R HV
Radial
Commercial, High Voltage
Commercial
No
WARNING: Cancer and reproductive harm – http://www.p65warnings.ca.gov.
ef26097b-3862-4ee0-b0ad-404a563ece0f
Lead (SnPb)
N/A
No

Specifications			
Capacitance	1000 pF		
Capacitance Tolerance	10%		
Voltage DC	10000 VDC		
Dielectric Withstanding Voltage	12000 VDC		
Temperature Range	-55/+125°C		
Temperature Coefficient	X7R		
Dissipation Factor	2.5%		
Insulation Resistance	100 GOhms		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.