





ISSUE NUMBER	
ORIGINAL	1






.XX ±0.13 .XXX ±0.05

## NOTES:


MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ" GOLD PLATED



OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	50Ω (IMPEDANCE)
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.
INSULATOR RESISTANCE: DIELECTRIC	$5000M\Omega$ min.

1000V AC rms



				SW REFERENCE NO.: 629 COMBO ASSEMBLY		
	-		DRAWN: C.B	DATE: JAN. 01/201	19	
			CHECKED:	DATE:		
	EDACINC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
	TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 629-43W	2640-5ND	ISSUE	
	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 629-43W	2640-5ND	1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

	EDAC TORONTO, CANA
YOUR CONNECTION	ON TO QUALITY &

WITHSTANDING VOLTAGE:

