

TOLERANCE UNLESS OTHERWISE SPECIFIED .X ±0.25 .XX ±0.13 .XXX ±0.05


THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER

ORIGINAL

(1)



10.67 3.20 ٩ ۲

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE:


POWER/CO-AX CONTACT RATING: 40A (CURRENT) (IF PRESENT)

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.

-55°C ~ 125°C

1000V AC rms



| | COMBINATION D-SUB | | | SW REFERENCE NO.: 630 COMBO ASSEMBLY | | | | |
|---|--------------------|---|--|--------------------------------------|----------|--------------------|----|-------|
| | | | | DRAWN: C.B | | DATE: JAN. 01/2019 | | 19 |
| | | | | CHECKED: | | DATE: | | |
| E | | EDAC INC TORONTO, ONTARIO CANADA D QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1 | :1) | SHEET 1 | OF | 2 |
| | | | | DRAWING NUMBER: 630-8W8- | | -240-4N5 | | ISSUE |
| | YOUR CONNECTION TO | | | PART NUMBER: | 630-8W8- | -240-4N5 | | 1 |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

