	т Q т т				
4			4		
ω		LAYOUT SHOWN AS EXAMPLE	3		
	Keying Shown as example				
	CHARACTERISTICS Connector dimension				
	-Standard : Based on MIL-DTL-38999 Series III Dim Nominal -Shell Material : Aluminium ØS 29.4 Max -Shell Plating : Olive drab Cadmium Z 31 Max -Insulator : Thermoplastic VV THREAD M18x1-6g -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed PN: 8D513W03AA 			
N	-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours	A 18-10-2016 First Release			
		ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING			
		TITLE Aluminium Plug 8D series			
<u> </u>	BASIC SERIES: 8D 5 - 13 W 03 A A SHELL TYPE : Plug with RFI Shielding - - 13 W 03 A A	SCALE General linear NPRDS / PROJECT NA Tolerances: 859	1		
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13 CONTACT TYPE : PIN(500 Matings)	SOURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission			
	PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 13-03	03 FORMAT SOURIAU DRG N° SHEET			
,		A3 8D513W03AA-C 1/2	I		

	т	۵	н г	т	D	C	
		Contact Layout					
4							
	Ctc A B C	3#16 13-03 X Y 2.39 1.47 0 -2.79 -2.39 1.47					
ω							
-	-						
-						SOURIAU shall not b due to a use of th the Specifications issue (professional	e Products v ed by either
N							Coun FR
						PN:	8D513
					A 18-10-201 ISS DATE Designed By:	L6 First Release Latest modification - b Date:	у
					TITLE		Alumi
<u> </u>					SCALE NA		General linear Tolerances: ±
					SOURIAL	J WWW.SO	URIAU.
					FORMAT	S	OURIA

G

Н

F

Е

A3

D

С

