



C930ZG35500ZA0X

C93, Film, Metallized Polypropylene, AC Filter, 50 uF, -5/+15%, 320 VAC, 400 VDC





Note: Please contact KEMET for case type

Click here for the 3D model.

Dimensions	
D	60mm +/-0.5mm
L	98mm +/-2mm
S	18.8mm NOM

Packaging Specifications		
Packaging	Bulk, Bag	
Packaging Quantity	40	

General Information		
Series	C93	
Dielectric	Metallized Polypropylene	
Style	Can	
Features	Single Phase PFC	
RoHS	Yes	
Lead	Fast On (2+2)	
AEC-Q200	No	
Component Weight	195 g	
Miscellaneous	Contact KEMET for case type and additional dimensional data.	

Specifications			
Capacitance	50 uF		
Capacitance Tolerance	-5/+15%		
Voltage AC	320 VAC		
Voltage DC	400 VDC		
Temperature Range	-25/+55°C		
Rated Temperature	55°C		
Max dV/dt	30 V/us		
Ripple Current	4.5 Amps		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.