


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00129	Connector, dc plug, 5.5x2.5xL18.5 mm, molding style, spring contacts	1	
2	30-00338	Wire, 1C TS, 20 AWG, UL1185, 300V, 80C, 2.95 mm, shielded, VW-1, PVC	1	
3	24-00357	Overmold, dc plug, 5.5 mm	1	PVC, black
4	Heat shrink	Heat shrink, black	1	covers end of jacket
5	Heat shrink	Heat shrink, black	1	covers shield



Notes:
Functionally equivalent components may be substituted
Cable rated for 48 V, 7.0 A

Wiring Diagram	
50-00129	wire color
center	white
sleeve	shield (black)

Revision:	Date:	Description:	Prepared:	Notes: RoHS compliant Function test: no open, no short circuit, no intermittent	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	4/19/2021	Initial release	Verified:		
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 915 mm, 5.5x2.5x9.5 mm 50-00129 dc plug to stripped tinned, 20 AWG, 30-00338 wire	Size: A
					Part number: 10-03914
					Scale: 1:1
					Sheet 1 of 1

5

4

3

2

1