


N	0	T	E	S	2

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED			
OPERATING TEMPERATURE:	-55°C ~ 125°C			
POWER/CO-AX CONTACT RATING: (IF PRESENT)	10A (CURRENT)			
SIGNAL CONTACT CURRENT RATING SIGNAL CONTACT RESISTANCE:	: 5A PER CONTACT 10mΩ MAX.			
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.			
WITHSTANDING VOLTAGE:	1000V AC rms			

	COMBINATION D-SUB			SW REFERENCE NO.: 630 COMBO ASSEMBLY				
C				C.B	DATE: JAN. 01/2019			
					DATE:			
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC. AND	SCALE: (II	N C.A.D. 1:1)	SHEET 1 OF	2		
	TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING N	UMBER: 630-2WK2	2240-1N6	ISSUE		
YOUR CONNECTION TO QU	ALITY & SERVICE		PART NUMB	ER: 630-2WK2	2240-1N6	1		





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



