

DESCRIPTION

PRODUCT COVERED:

Component Connectors - Sub-D, Cat. Nos. V23529-R, V23539-S and V23529-T

GENERAL:

These devices are multi-pole connectors employing contacts of the press-fit termination type for use with printed circuit boards where the acceptability of the combinations is determined by Underwriters Laboratories Inc.

ENGINEERING CONSIDERATIONS (NOT FOR UL REPRESENTATIVE USE):

Use - For use only in complete equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.

Conditions of Acceptability - In order to be judged acceptable as a component of electrical equipment, the following conditions should be met.

1. These devices should be used only where they will not interrupt the current.
2. These devices have not been tested for current-carrying capability.
3. The suitability of the mounting means shall be determined in the end use.
4. The acceptability of the grounding connection shall be determined by the end product use engineer.
5. The placement of these devices within the equipment enclosure should be such that spacings between the live parts and the equipment are suitable for the particular application.
6. The adjacent poles may be used at potentials not exceeding 250 volts based on the spacings requirements of Paragraph 11.1 of UL 1977. Dielectric testing has not been performed.

7. The electrical and mechanical contact between the connector and the printed circuit board is to be judged in the end-use equipment.
8. The suitability of the insulating materials used in the molded bodies shall be judged in the end-use equipment.
9. The operating temperature of these devices should not exceed the temperature ratings of the insulating materials. These materials may be used interchangeably at a maximum temperature of 140°C.