	т	m		0			
	ØS						
				LAYOUT SH	OWN AS EXAMPLE		
	Keying Shown a	s example					
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	F	Connector dimension Dim Nominal					
-Shell Material: Composite-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy		ØS         44.9 Max           Z'         31.5 Max           VV THREAD         M34x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum						on & Control List ot Listed	
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				PN: 8D523M32HN			
-Temperature Range -65°C to +200°C			A 06-10	-2016 First Release			
-Salt Spray : 2000 hours			ISS DA Designed By:	TE Latest modification - by Date:	C	USTOMER DRAWING	/IOD N°
		TITLE     Composite Plug 8D series					
BASIC SERIES: 8D 5 - 23 M SHELL TYPE : Plug with RFI Shielding	32 H N		SCALE		eral linear erances: ±	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact ORIENTATION :				SOURIAU         WWW.SOURIAU.COM         This document is the property of SOURIAU it must not be reproduced or			
SHELL SIZE : 23		CONTACT TYPE : PIN (1500 Mati		SOL	JRIAU DRG N°	communicated without permissi	ion SHEET
PLATING : M = Nickel		CONTACT LATOOT 2					

-	т	۵	п П	m		0
		Contact Layout				
4		$\begin{array}{c} & & & & & & & & \\ & & & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & &$				
	$\begin{array}{rrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrr$	$\begin{array}{c c c c c c c c c c c c c c c c c c c $				
ω	M325 (8.26) N100 (2.54) P +.000 (0.00) R +.150 (3.81)	$\begin{array}{cccccccccccccccccccccccccccccccccccc$				
	F					
						SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D5231
					A 06-10-20 ISS DATE Designed By:	016 First Release Latest modification - by Date:
					TITLE	Compo
<b>→</b>					SCALE NA	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.
					FORMAT A3	SOURIAU 8D523M
L	Н	G	F	E	D	C

