



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Black Zinc Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours
- Mass : 15.75 g ± 10%

| Connector dimension |               |
|---------------------|---------------|
| Dim                 | Nominal       |
| P                   | 3.25±0.2      |
| PP                  | 4.93±0.2      |
| R1                  | 23.01         |
| R2                  | 20.62         |
| S                   | 28.6±0.3      |
| V                   | 20.83+0/-1.25 |
| W                   | 2.1/2.5       |
| Z                   | 31.5 Max      |
| VV THREAD           | M18x1-6g      |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

**PN: 8D013Z98PE**

|                     |            |                                       |                               |
|---------------------|------------|---------------------------------------|-------------------------------|
| A                   | 17-10-2016 | First Release                         |                               |
| ISS                 | DATE       | Latest modification - by              | MOD N°                        |
| Designed By:        |            | Date:                                 | <b>CUSTOMER DRAWING</b>       |
| <b>TITLE</b>        |            | Aluminium Receptacle 8D series        |                               |
| SCALE               | NA         | General linear Tolerances: ±--        | NPRDS / PROJECT<br><b>859</b> |
| <b>SOURIAU</b>      |            | WWW.SOURIAU.COM                       |                               |
| FORMAT<br><b>A3</b> |            | SOURIAU DRG N°<br><b>8D013Z98PE-C</b> |                               |
|                     |            |                                       | SHEET<br>1/2                  |

BASIC SERIES: 8D 0 - 13 Z 98 P E

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

SHELL SIZE : 13

PLATING : Z = Black Zinc Nickel

ORIENTATION : E

CONTACT TYPE : PIN(500 Matings)

CONTACT LAYOUT : 13-98

Contact Layout



| Contacts<br>(Insert arrangement 13-98) |             |             |
|--|-------------|-------------|
| Contact position ID                    | Location    |             |
|  | X-axis (mm) | Y-axis (mm) |
| A                                      | +000 (0.00) | +195 (4.95) |
| B                                      | +125 (3.18) | +150 (3.81) |
| C                                      | +193 (4.90) | +030 (0.76) |
| D                                      | -104 (4.17) | -105 (2.67) |
| E                                      | +000 (0.00) | -135 (3.43) |
| F                                      | -164 (4.17) | -105 (2.67) |
| G                                      | -193 (4.90) | +030 (0.76) |
| H                                      | -125 (3.18) | +150 (3.81) |
| J                                      | +065 (1.65) | -015 (0.38) |
| K                                      | -065 (1.65) | -015 (0.38) |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 13         | -98             | 10                 | 20            | I              | All              | MS20051-98 |

Panel Cutout



| Dim | Nominal    |
|-----|------------|
| ØA  | 23.42 min  |
| ØAA | 19.05 min  |
| R1  | 23.01      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D013Z98PE

|                |                                       |                            |   |
|----------------|---------------------------------------|----------------------------|---|
| A              | 17-10-2016                            | First Release              |   |
| ISS            | DATE                                  | Latest modification - by   | MOD N°  |
| Designed By:   |                                       | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Aluminium Receptacle 8D series</b> |                            |   |
| SCALE          |                                       | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |                                       | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D013Z98PE-C</b>    |                            | SHEET 2/2   |