



Recommended Cable Stripping Dim's

- NOTES: Finish (Plating Thickness in Micro-inches)
1. Brass
  2. Albaloy Plating (Copper-Tin-Zinc) Pl. 80 Min, Thick
  3. Gold Pl. 5 Min Thick over Copper Pl. 50 Min. Thick
  4. Teflon
  5. Passivated

Crimped Ferrule  
Hex. Crimp Size .213 (5.4)  
Crimped Contact Pin  
Hex. Crimp Size .100 (2.54)

RoHS Compliant

9	Ferrule	Note 1	Note 2	1															
8	Contact Pin	Note 1	Note 3	1															
7	Retainer Ring	SUS 304	Note 5	1															
6	Gasket	Silicone	Red	1															
5	Contact Body	Note 1	Note 2	1															
4	Insulator	Note 4	Natural	1															
3	Barrel	Note 1	Note 2	1															
2	Body	Note 1	Note 2	1															
1	Shell	Note 1	Note 2	1															
No.	Description	Material	Finish	Q'ty	Drawing No.	Scale	2.5/1	Issue	A	Part No.		Approved		Date	12-14-2018	Title			
										Unless Otherwise Specified Tolerances		Checked		Date	12-14-2018	NTE Electronics			
										0.5-6 = ±0.2		Drawn		Date	12-14-2018	N Crimp Plug			
										6-30 = ±0.4						(For RG-58C/U Cable)			
										30-120 = ±0.6						Drawing No.			
										120-315 = ±1						06-N002			
										315-1000 = ±1.6						File No.			
										1000-2000 = ±2.4									