


.XX ±0.13 .XXX ±0.05

NOTES:


MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED



OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	40A (CURRENT)
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.
INSULATOR RESISTANCE:	$5000M\Omega$ min.

10mΩ MAX. 5000MΩ min. 1000V AC rms



	COMBINATION D-SUB		SW REFERENCE NO.: 629 COMBO ASSEMBLY				
			DRAWN: 0	C.B	DATE: JAN. 01/20	19	
			CHECKED:		DATE:		
	EDAC INC	OR USED AS THE BASIS FOR THE	SCALE: (IN	N C.A.D. 1:1)	SHEET 1 OF	2	
	TORONTO, ONTARIO CANADA		DRAWING NUMBER: 629-47W1240-4TE		1240-4TE	ISSUE	
	YOUR CONNECTION TO	QUALITY & SERVICE	MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBI	ER: 629-47W1	1240-4TE	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

