


THIS SERIES FULLY CONFORMS TO


THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.






N	0	ΓЕ	S:	

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PL/	
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	10A (CURRENT)	
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.	
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.	
WITHSTANDING VOLTAGE:	1000V AC rms	



	COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY			
COMBINATION			DATE: JAN. 01/20	19		
			DATE:			
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2		
	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 630-2W2-250-1N2 I		ISSUE		
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-2W2-	-250-1N2	1		



HS

COMPLIANT

Г

