



# Product: <u>8489</u>

Electronic, 4 C #18 Str TC, PVC Ins, PVC Jkt, CMG

😭 Request Sample

## **Product Description**

Electronic, 4 Conductor 18AWG (19x30) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

## **Technical Specifications**

### Product Overview

Outtable Annlingtions	
Suitable Applications:	low voltage analog signals (4-20ma, 0-10v,); low voltage control (24v,); line level audio; voice communications; panel wiring
onstruction Details	
onductor	
Element Number of Ele	ement Size Stranding Material
Conductor(s) 4	18 AWG 19x30 TC - Tinned Copper
sulation	
Element Materia Conductor(s) PVC - Polyviny	al         Nom. Thickness         Nom. Insulation Diameter         Color Code           / Chloride         0.018 in (0.46 mm)         0.081 in (2.1 mm)         Black, White, Red, Green
outer Jacket	
	om. Thickness Nom. Diameter
PVC - Polyvinyl Chloride 0.03	32 in (0.81 mm) 0.264 in (6.71 mm)
Overall Cable Diameter (Nomi	inal): 0.264 in (6.71 mm)
Electrical Characterist	tics
lectricals	
Element Nom. Conduct Conductor(s) 7.06 Ohm/1000	tor DCR         Nom. Capacitance Cond-to-Cond         Max. Current           0ft         26 pF/ft (85 pF/m)         11.2 Amps per Conductor at 30°C
oltage	
UL Voltage Rating	
300 V (CMG), 300 V (UL AWN	A 2598)
Nechanical Character	istics
emperature UL Temperature Operatir	
60°C -20°C to +6	
end Radius	
Stationary Min. Installation	
2.6 in (66 mm) 2.6 in (66 m	
2.6 in (66 mm) 2.6 in (66 m	
2.6 in (66 mm) 2.6 in (66 m Max. Pull Tension: Bulk Cable Weight:	99 lbs (45 kg) 44 lbs/1000ft

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	UL 1685 UL loading , FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 725, Article 800, CMG, CL3
AWM Compliance:	AWM 2598
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	88489, 82489

#### History

Update and Revision:

Revision Number: 0.514 Revision Date: 04-14-2023

#### **Part Numbers**

#### Variants

ltem #	Color	Putup Type	Length	UPC
8489 060100	Chrome	Reel	100 ft	612825208754
8489 060250	Chrome	Reel	250 ft	612825208778
8489 060500	Chrome	Reel	500 ft	612825208785
8489 060U500	Chrome	UnReel	500 ft	612825208747
8489 0601000	Chrome	Reel	1,000 ft	612825208761
8489 060U1000	Chrome	UnReel	1,000 ft	612825208730
8489 0605000	Chrome	Reel	5,000 ft	612825208792

#### © 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.