BGA Heat Sink - High Performance Straight Fin w/Thermal Tape





ATS Part#: ATS-54330R-C1-R0

Description: 33.00 x 33.00 x 19.50 mm BGA Heat Sink - High Performance Straight Fin

w/Thermal Tape

Heat Sink Type: Straight Fin
Heat Sink Attachment: Thermal Tape

Equivalent Part Number: ATS-54330R-C2-R0

*Image above is for illustration purpose only.

Features & Benefits

- High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- · Designed specifically for BGAs and other surface mount packages
- · Comes preassembled with high performance thermal interface material

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	4.1 °C/W	3 °C/W	2.6 °C/W	2.3 °C/W	2.1 °C/W	2 °C/W	1.8 °C/W
	Ducted Flow	2.3	N/A	N/A	N/A	N/A	N/A	N/A

Product Detail

Schematic Image Dimension		Dimension B	Dimension C	Dimension D	TIM	Finish
	33.00 mm	33.00 mm	19.50 mm	N/A mm	T412	BLACK-ANODIZED
*Image above is for illustration purpose only.	 Dimension ATS-5433 (Saint-Go Thermal papplication ATS reserved ATS certifies 	BOR-C2-R0 is the exbain C675). Derformance data aren. The right to updance. The fies that this heat sires.	height from the botto act heat sink assem e provided for reference ate or change its pro-	ence only. Actual pe oducts without notice S-6 and REACH cor	ent thermance to impro	al interface material e may vary by



