



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 2-18NS-2A         |
| B   | 32.5              |
| C   | 1 3/4-18NS-2A     |
| D   | 11                |
| E   | 22.2              |
| F   | 4                 |
| G   | 62                |
| H   | 44.5              |
| I   | 57                |
| K   | 4.4               |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3   | DICHTKÖRPER / GROMMET                   |
| 4   | ENDRING / ENDRING                       |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 8   | DOSENGEHÄUSE / SHELL                    |
| 14  | F-ENDGEHÄUSE / F-ENDBELL                |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

**Material Specification:**  
 Shell Material: Aluminium alloy  
 Shell Plating: Olive drab chromate coating over cadmium plating  
 Insulator Material: Neoprene  
 Contact Material: Copper alloy  
 Contact Plating: Hard silver

|  |  |   |                         |
|--|--|---|-------------------------|
| all dimensions are in mm<br>Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  |  | drawing for<br>CUSTOMER   |                         |
| <br><b>ITT</b><br><i>Engineered for life</i><br><small>ITT CANNON GmbH<br/> D - 71384 Weinstadt/Germany</small> |  | description CA3100F32-6S  |                         |
|  |  | Wall mounting receptacle<br>Endbell for flex tube<br>Solder Cup / Socket / Layout: 32-6           |                         |
| © All rights reserved. Reproduction or issue to third in any form<br>whenever is only permitted with written authorization of ITT Cannon   |  | <br>page 1/1 | revision 929 11. Jun 19 |