

www.lemo.com

CFB.M02.GLA.C72GZ

SUMMARY

Wires

 Low
 2

 High
 0

 Coax
 0

Triax 0

Quad 0 Fiber 0

Fluidic 0

Series 2P

Termination type Male solder

IP rating 66

Cable Ø 5.30 - 7.20 mm

Status active

Alternative part

Matching parts CNB.M02.GLLG



Image is for illustrative purpose only

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model CF*: Straight plug with cable collet, watertight (IP 66) and nut for fitting a bend relief

Keying 3 keys (alpha=0, gamma=60; Plug: male contacts; Receptacle: female contacts)

Housing Material PSU (Polysulfone), grey

Variant

Weight 9.23 g

Performance

Configuration 2P.M02: 2 Low V.

Insulator L: PEEK for solder contacts

Rated Current 30 Amps

Specifications

Contact Type: Solder

Contact Dia.: 2.0 mm (0.078in) Bucket Dia.: 1.8 mm (0.070in)

Test voltage (kV rms) Contact-contact: 2.1

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Others

Endurance (Shell): >1000 mating cycles


F ret (min): 150 N F ret (max): 250 N


Steam sterilization: 20 times (with potting on rear connection)

IP Rating: 66

DRAWINGS

Draws







Dimensions

	А	L
mm.	18	57
in.	0,71	2,24

RECOMMENDED BY LEMO

Tools

None

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

CMN.02.T14.072PGCE CMN.02.T14.072PGZE	PVC	GREY Grey	
CMN.02.T14.072PNCE	PVC	Black	-
CMN.02.T14.072PNZE		Black	
CMN.02.T14.072QGZE	TPR (medical)	Grey	-
CMN.02.T18.064UNCU			
120 184	PVC	Black	~
120 500	PVC	Grey	
120 751	PVC	Grey	
220 151	PVC	Grey	-
220 750	PVC	Grey	-

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.