



Click [here](#) for the 3D model.

### Dimensions

|    |                 |
|----|-----------------|
| L  | 13mm -0.5mm     |
| H  | 12mm -0.5mm     |
| T  | 6mm -0.5mm      |
| S  | 10mm +/-0.4mm   |
| LL | 4mm +2mm        |
| F  | 0.6mm +/-0.05mm |
| G  | 0.5mm NOM       |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 1000      |

### General Information

|                  |                          |
|------------------|--------------------------|
| Series           | F871                     |
| Dielectric       | Metallized Polypropylene |
| Style            | Radial                   |
| Features         | MKP EMI Safety           |
| RoHS             | Yes                      |
| Lead             | Cut/Short                |
| Safety Class     | X1                       |
| Qualifications   | ENEC, UL, cUL, CQC       |
| AEC-Q200         | No                       |
| THB Performance  | No                       |
| Component Weight | 1.409 g                  |
| Miscellaneous    | ClimCat: 40/110/56/C.    |
| Shelf Life       | 104 Weeks                |

### Specifications

|                       |              |
|-----------------------|--------------|
| Capacitance           | 0.025 uF     |
| Capacitance Tolerance | 20%          |
| Voltage AC            | 330 VAC (X1) |
| Voltage DC            | 800 VDC      |
| Temperature Range     | -40/+110°C   |
| Rated Temperature     | 110°C        |
| Dissipation Factor    | 0.3% 1KHz    |
| Insulation Resistance | 30 GOhms     |
| Max dV/dt             | 500 V/us     |