



Click [here](#) for the 3D model.

| Dimensions | |
|------------|------------------|
| L | 13mm +0.2/-0.5mm |
| H | 9mm +0.1/-0.5mm |
| T | 4mm +0.2/-0.5mm |
| S | 10mm +/-0.4mm |
| LL | 25mm +2/-1mm |
| F | 0.6mm +/-0.05mm |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 1800 |

| General Information | |
|---------------------|---------------------------------|
| Series | R76 |
| Dielectric | Double Metallized Polypropylene |
| Style | Radial |
| Features | Automotive Grade, Pulse |
| RoHS | Yes |
| Lead | Wire Leads |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |

| Specifications | |
|-----------------------|---------------------------------------|
| Capacitance | 8200 pF |
| Capacitance Tolerance | 10% |
| Voltage AC | 400 VAC |
| Voltage DC | 630 VDC |
| Temperature Range | -55/+110°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz |
| Insulation Resistance | 100 GOhms |
| Max dV/dt | 4000 V/us |
| Resistance | 77.64 mOhms (100kHz) |
| Ripple Current | 1.8 Amps (100kHz 85C), 33 Amps (Peak) |
| Inductance | 9 nH |