

ATGBICS SFP-10G-BXD-I-C network transceiver module Fiber optic 10000 Mbit/s SFP+

Brand : ATGBICS Product code: SFP-10G-BXD-I-C

Product name: SFP-10G-BXD-I-C



Cisco Compatible Transceiver, SFP+, 10GBase-BX-D, BiDi, Tx1330nm/Rx1270nm, 10km, SMF, DOM, Ind

ATGBICS SFP-10G-BXD-I-C network transceiver module Fiber optic 10000 Mbit/s SFP+:

ATGBICS SFP-10G-BXD-I 1000Base-BX SFP supports a distance of up to 10km over single mode fibre (SMF) using a wavelength of Tx1330nm/Rx1270nm via an LC connector. This bidirectional unit must be used with another transceiver or network appliance of complimenting wavelengths. This product is suitable for rugged environments and can operate at temperatures between -40C to +85C. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of CiscoSFP-10G-BXD-I= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Power	
Maximum data transfer rate * Interface type * Single-mode fiber (SMF) supported	ximum data transfer rate * 10000 Mbit/s xrface type * SFP+ gle-mode fiber (SMF) supported ti-mode fiber (MMF) supported xer optic connector xer transceiver standard ximum transfer distance xwavelength (max) xwavelength (max) 1270 nm	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
		Operational conditions	
Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Tx wavelength (max) Rx wavelength (max) Ethernet interface type		Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 °C 185 °C -40 - 85 °C -40 - 85 °C 0 - 95%
Digital Diagnostics Monitoring (DDM)	· ·	Weight & dimensions	
	ı	Width	13.4 mm
Features		Depth	56.5 mm
Product colour Housing material	Silver Metal	Height Weight	8.5 mm 19 g
Plug and Play		Packaging data	
Hot-swap		Number of products included	1 pc(s)
Easy to install		Package type	Box
Country of origin Brand compatibility		Technical details	
		Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.