

NOTES:

MATERIAL:	
HOUSING:	
SHELL:	
CONTACT:	
OPERATING TEMPERATURE:	

.XX ±0.13

.XXX ±0.05

10.70

5.80

POWER/CO-AX CONTACT RATING:	20A (CURRENT)
(IF PRESENT)	
SIGNAL CONTACT CURRENT RATING:	5A PER CONTACT
SIGNAL CONTACT RESISTANCE:	10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:



THERMOPLASTIC POLYESTER, UL94V-0

COPPER ALLOY, 30µ GOLD PLATED


STEEL, NICKEL PLATED

-55°C ~ 125°C

5000MΩ min.

1000V AC rms

	COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY			
			DRAWN: C.B	DATE: JAN. 01/20	19	
			CHECKED:	DATE:		
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC. AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
	YOUR CONNECTION TO QUALITY & SERVICE	OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS	DRAWING NUMBER: 630-3W3	-650-2NA	ISSUE	
			PART NUMBER: 630-3W3	-650-2NA	1	



ũ COMPLIANT

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

