

Datasheet revision 1.0 www.chipquik.com

## Polyimide Film Tape 3.000" (3") x 36 Yards

### **Product Highlights**

- Amber colored 2 mil thick (1 mil without adhesive) polyimide film tape.
- Silicone adhesive provides superior high temperature performance, reducing adhesive transfer to help eliminate cleaning.
- Dimensionally stable at high temperatures.
- Flame retardant.
- · Chemical and radiation resistant.
- Polyethylene tape core for better roll stability.

#### **Common Uses**

- High Temperature Masking.
- Printed circuit board (PCB) solder masking for wave solder or solder dip processes.
- As a release surface for parts fabricated and cured at elevated temperatures.
- High temperature insulating applications.



Backing, Carrier:

Adhesive:

Color:

Total Thickness:

Backing Thickness (Thickness - Adhesive):

Width:

Polyimide Film
Silicone
Amber
0.002"
0.001"
3"

Length: 36 yards (33 meters, 108 feet)

Elongation at break: >50%

Tensile Strength: 34 lb/in width (600 N/100mm)
Adhesion to Steel: 29 oz/in width (32 N/100mm)

Voltage Withstand: 5000 volts

Operating Temperature Range: -73C to +260C (-100F to +500F)

Maximum Temperature: +280C (536F)

Flame Retardant: Yes Packaging: Roll

#### **Shelf Life**

>36 months

#### **Transportation**

This product has no shipping restrictions. Shipping below 0C (32F) or above 25C (77F) for normal transit times by ground or air will not impact this product's stated shelf life.



# **CHIPQUIK®** Polyimide Film Tape Orderable Part Numbers

Product Image	Part Number	Product Image	Part Number
	CQT1-0.125		CQT1-1.500
	1/8" x 36 Yards		1-1/2" x 36 Yards
	CQT1-0.250		CQT1-2.000
	1/4" x 36 Yards		2" x 36 Yards
	CQT1-0.375	B	CQT1-3.000
	3/8" x 36 Yards		3" x 36 Yards
	CQT1-0.500		CQT1-6.000
	1/2" x 36 Yards		6" x 36 Yards
	CQT1-0.750		CQT1-12.000
	3/4" x 36 Yards		12" x 36 Yards
	CQT1-1.000		CQT1-20.000
	1" x 36 Yards		20" x 36 Yards
	CQT1-1.250		
	1-1/4" x 36 Yards		