

## Cat6 RJ45 Pass-Through FTP Modular Plug, 100 Pack

### MODEL NUMBER: N232-100-FTP











Clear RJ45 Cat6 connectors terminate round solid or stranded conductor cabling in data and voice Ethernet applications.

#### **Features**

### 100 Pack of RJ45 FTP Modular Plugs for Terminating Solid or Stranded Cat6 Cable

These FTP modular connectors make it easy to terminate solid or stranded conductor Cat6 cable in your data or voice Ethernet application. The RJ45 pass-through FTP (Foiled Twisted Pair) plugs work with most RJ45 crimping tools (except AMP) and custom-length 24–26 AWG FTP and F/UTP Cat6 cabling at up to 6.2 mm jacket diameter. Conveniently packed in a rugged plastic bag that fits perfectly in your toolbox, these durable clear connectors feature 50-micron gold-plated contacts for optimal signal transmission.

# Premium Protection from EMI/RFI and Other Noise Helps Your Equipment Perform Better Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. The FTP plugs' foil shielding blocks disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer. Nearend crosstalk (NEXT) levels are practically eliminated, so you don't have to worry about keeping your cables separated in crowded pathways or spend valuable time on field testing.

### **Highlights**

- 100 Cat6 RJ45 pass-through FTP modular plugs in an easyto-pack plastic bag
- Work with most RJ45 crimping tools and 24–26 AWG FTP and F/UTP Cat6 cables
- Shields against disruptive EMI/RFI noise that can inflict hardware damage or data loss
- Staggered nose pattern reduces near-end crosstalk for clearer transmission
- Ideal for use with solid or stranded conductor Cat6 cable in your Ethernet application

### **Applications**

Terminate solid or stranded conductor cabling in Cat6 network applications

### **Package Includes**

(100) Cat6 RJ45 pass-through FTP modular plugs

### **Specifications**

OVERVIEW	
UPC Code	037332260727
Technology	Cat6; Cat6a
PHYSICAL	
Cable Shielding	FTP
Cable Outer Diameter (OD)	< 6.2 mm



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Wire Gauge (AWG)	24 - 26	
ville Gauge (AVVG)	24 - 20	
ENVIRONMENTAL		
Operating Temperature Range	-40 to 185 °F (-40 to 85 °C)	
Storage Temperature Range	41 to 86 °F (5 to 30 °C)	
Relative Humidity	15 to 65% RH, Non-Condensing	
WARRANTY		
Product Warranty Period (Worldwide)	Limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>