

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0919993474](#)  
**Status:** **Active**  
**Overview:** [RAST Connector System](#)  
**Description:** [Appli-Mate RAST 5 Header, Vertical, 6 Circuits, Silver \(Ag\) Plating, Glow-Wire Capable](#)

**Documents:**

[Drawing \(PDF\)](#) [Packaging Specification PK-90858-001-001 \(PDF\)](#)  
[Product Specification PS-99020-0037-001 \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)  
[Packaging Specification PK-90833-001-001 \(PDF\)](#)

**Agency Certification**

CSA LR19980  
 UL E29179

**Application tooling part link**

Application Tooling Part Link 216658-0200


**General**

Product Family PCB Headers  
 Series [91999](#)  
 Application Power, Wire-to-Board  
 Comments """"""This Molex product is manufactured from material that has the following ratings, tested by independent agencies:. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. <P><P> The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). <P> If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for possible product options.""""""

Overview [RAST Connector System](#)  
 Product Name RAST 5  
 UPC 884982524859

**Physical**

Breakaway No  
 Circuits (Loaded) 6  
 Circuits (maximum) 6  
 Color - Resin Natural  
 Durability (mating cycles max) 10  
 First Mate / Last Break No  
 Flammability 94V-0  
 Glow-Wire Capable Yes  
 Guide to Mating Part No  
 Keying to Mating Part Yes  
 Lock to Mating Part Yes  
 Material - Metal Brass  
 Material - Plating Mating Silver



Series image - Reference only

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
 D(2021)4569-DC (8  
 July 2021)

**Halogen-Free**

**Status**

**Not Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[91999 Series](#)

**Mates With**

Appli-Mate RAST 5 IDT Housing [91778](#) ,  
[91779](#)

**Use With**

RAST Standard Interface

**Application Tooling | FAQ**

*Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.*

**Global**

**Description**

**Product #**

RAST 5 Power  
 Semi-Automatic IDC  
 Machine

[2166580200](#)

Material - Plating Termination	Nickel
Material - Resin	Nylon
Net Weight	11.970/g
Number of Rows	1
Orientation	Vertical
PC Tail Length	3.90mm
PCB Locator	Yes
PCB Retention	None
PCB Thickness - Recommended	1.40mm
Packaging Type	Bag
Pitch - Mating Interface	5.00mm
Pitch - Termination Interface	5.00mm
Shrouded	Fully
Stackable	No
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-20° to +120°C
Termination Interface: Style	Through Hole

**Electrical**

Current - Maximum per Contact	16.0A
Voltage - Maximum	250V AC

**Material Info****Reference - Drawing Numbers**

Packaging Specification	PK-90833-001-001, PK-90858-001-001
Product Specification	PS-99020-0037-001

This document was generated on 10/18/2021

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**