

AR884CHSSL



Sample image

Order symbol: AR884CHSSL

Product nbr: 8561088

Description: PC Enclosure

Remarks: Hinged opaque cover w/S.S. Lockable latch

EAN: 6418074066718

El. number:

- Finland:
- Denmark:
- Sweden:

Including: Hinged cover. Base with 10-32 brass inserts, latched cover with formed in place PUR gasket, stainless hinge pin. Quick release latches. Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

ARCA-8x8_combi

Dimensions:	Height	Width	Depth
mm:	203	203	102
inch:	8	8	4

Materials:

Material:	Polycarbonate
Base colour:	RAL 7035 -light grey
Cover colour:	RAL 7035 -light grey
Gasket material:	Polyurethane

Temperatures:

Temperature °C (short term)::	-40 ... 140
Temperature °C (continuous):	-40 ... 80
Temperature °F (short term):	-40 ... 250
Temperature °F (continuous):	-40 ... 175

Accessories:

ALBP88	Aluminum Back Panel (175 x 175)
ABP88	Painted Steel Back Panel (175 x175)
ASP88	Aluminum Swing Panel (204.4 x 204.5 x 0)
ASPHK8	Swing Panel Kit w/o Panel
APBP88	PVC Back Panel (175 x 175)
ADFP88	Dead Front Panel w/ screws (175 x 175 x 0)
ASPK88	Swing Panel Kit incl. Panel
AMFL8	8" Mounting Flange Set

Rating:

Ingress protection (EN 60529):	IP66; IP67;
Impact Resistance (EN 62262):	IK09;
Electrical insulation:	Not insulated
Halogen free (DIN/VDE 0472, Part 815):	1
UV resistance:	UL 508
Flammability Rating:	UL 508
Glow Wire Test (IEC 695-2-1) °C:	960 °C
NEMA Class	NEMA 4, 4X, 6, 6P, 12, 12K

Certificates:

ARCA_CertificateofCompliance