



- 1 COPPER ALLOY PER ASTM B301
- 2 1.27 μm [50 μin] MIN GOLD PER ASTM B488
OVER 2.54 μm [100 μin] MIN NICKEL PER
QQ-N-290 ON ENTIRE STOCK.
- 3. APPLICATION TOOLING:
CRIMPING TOOL: M22520/23-01
DIE SET: M22520/23-02
LOCATOR: TYCO P/N 1738331-1
EXTRACTION TOOL: M81969/28-01
- 4. WIRE ACCOMMODATED: 8 AWG
STRIP LENGTH: 9.60 [.378] - 10.10 [.398]
- 5. THIS PRODUCT IS SOLD BY TYCO ELECTRONICS
UNDER A LICENSE FROM RADIAL SA

PRELIMINARY
NOT RELEASED FOR
PRODUCTION

Tyco PN - 1738019-1

DIMENSIONS : mm [inch]

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE	22MAR2004	REV	0
DRAWN BY		CHK		Tyco Electronics Corporation Harrisburg, Pa 17105-3608	
DIMENSIONS:		APPROVED		POWER CONTACT, PIN, CRIMP TERMINATION SIZE 5 GPR	
mm [INCHES]		PRODUCT SPEC		APPLICATION SPEC	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		SIZE	A0	SCALE	1:1
0 P.L.C.	± .005	WEIGHT		SHEET	1 OF 1
1 P.L.C.	± .005	CUSTOMER DRAWING		REV	0
2 P.L.C.	± 0.05 (.002)				
3 P.L.C.	± .005				
4 P.L.C.	± .005				
ANGLES	± .005				