**Mounting Option** .468 (11.89) Offset Card Guides **Contact Detail** Wire Hole .089x.014(2.29x0.36) - Tail LG=.213(5.41) .156 [3.96] Contact Spacing x .200 [5.08] Row Spacing 3.586 [91.08] 3.440 [87.38] 0.343[8.71] 0.473 [12.01] 



.175 [4.45] Point of Contact (Measured from bottom of Card Slot) Card Slot Accepts .054 [1.37] to .070 [1.78] Thick P.C. Board SECTION A-A

## 807 Series High Temp Card Edge Connector Part Number: 807-021-501-158 **See Accompanying Pages for:**

- **Contact Bend Details**
- **Mounting Options**
- **Features and Specifications**

YOUR CONNECTION TO QUALITY & SERVICE

NTS SHEET 1 OF 4 807 Assembly

J.LEE

807 ENG MASTER

DATE: AUG. 11/09





ISSUE NUMBE

ORIGINAL



## **Features**

- CSA Approved and UL Recognized
- .156 (3.96) Contact Spacing x .200 (5.08) Row Spacing
- Accepts .062 (1.57) Nominal Thickness P.C. Board
- Low Profile Insulator Body .473 (12.01), with Card Guides
- Contact Termination Options include P.C. Tail, Wire Hole, Wire Wrap, 90 Degree & Extender Board Bends
- Single or Dual Row Configurations
- Large Variety of Mounting Options
- Pre-assembled Card Guides Available
- Accepts Between Contact and In-Contact Polarizing Keys

## **Specifications**

- Insulator Material: DAP
- Contact Material: Copper, Nickel, Tin Alloy CA-725
- Contact Plating: Gold on the Mating Area, Tin on the Contact Tails, Nickel Underplate
- Current Rating: 5 Amperes Continuous
- Contact Resistance: 10 Milliohms Maximum
- Dielectric Withstanding Voltage: 1800 V AC rms at Sea Level Between Adjacent Contacts
- Insulation Resistance: 5000 Megohms Minimum
- Operating Temperature: -65 to +165 °C
- Insertion Force: 16 oz (4.45 N) Maximum per Contact Pair when Tested with a .070 (1.78) Thick Gauge
- Withdrawal Force: 1 oz (0.28 N) Minimum per Contact Pair when Tested with a .054 (1.37) Thick Gauge

807 Series High Temp Card Edge Connector Features and Specifications		ACAD REFERENCE NO. 807 ENG MASTER			
		DRAWN:	J.LEE	DATE: AU	G. 11/09
		CHECKED:		DATE:	
EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE:	NTS	SHEET .	4 OF 4
		DRAWING	NUMBER		ISSUE
		8	07 Assembly		1