T	۵	п	п	t		O	Φ		
	Z	ØS							
						LAYOUT SHO	WN AS EXAMPLE		
		Keying Show	vn as example						
CHARACTERISTICS			Connector dimension	_					
-Standard : Based on	MIL-DTL-38999 Series III		Dim Nominal						
-Shell Material -Shell Plating -Insulator -Contacts	nell Plating : Olive drab Cadmium 2 31 Max isulator : Thermoplastic VV THREAD M15x1-6g				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Seals & Grommet -Contact Plating	: Silicon Elastomer : Gold over copper Alloy 0.8µm minir	mum					Country Jurisd	iction & Control List Not Listed	
-Durability	: 500 Mating cycles					PN· 8D	511W04SEL]
-Delivered without So				r					
-Temperature Range -Salt Spray	_: -65°C to +175°C : 500 hours				A 17-10-201	6 First Release			
– -Mass	: 16.26 g ± 10%				ISS DATE Designed By:	Latest modification - by Date:		CUSTOMER DRAWING	MOD N°
					TITLE	A	Aluminium Plug 81		
			1		SCALE				
BASIC SERIES: SHELL TYPE : Plug wi	8D 5 - 11	1 W 04 S E		W/O Contacts	NA	-[(al linear ances:	NPRDS / PROJECT 859	
CONTACT TYPE : Sta				RIENTATION : E	SOURIAU			This document is the prop SOURIAU	
SHELL SIZE : 11			CONTACT TYPE : SOCKET	(500 Matings)	JUUNAU			it must not be reproduc communicated without pe	
	Olive drah Cadmium		CONTACT L	AYOUT : 11-04	FORMAT	SOU	RIAU DRG N°		SHEET
PLATING : W =					A3		11W04SEL-C		1/2

r	Ŧ	۵	г	m	D	0
		Contact Layout				
4	y.	$ \begin{array}{c} \bullet \\ \bullet \\$				
	Shell Arrangement Numb size no. 11 -4 4	n X-axis Y-axis (mm) (mm) +.065 (1.65) +.065 (1.65) 065 (1.65)065 (1.65) 065 (1.65)065 (1.65) 065 (1.65) +.065 (1.65) er of Size Service Contact Supersedes acts contacts rating location				
ω						
	1					
						SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D511V
					A 17-10-20 ISS DATE Designed By:	016 First Release Latest modification - by Date:
					TITLE	Alumir
<u> </u>					SCALE	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D511W
L	Н	G	F	E	D	C

	Φ			A			
							4
							<u> </u>
							3
any no	n-conformit	v or dar	nage				
which	does not co Parties or b	mply wi	th				
	technical n	-					
intry R	Jurisd	iction & Not Li	Control	List			2
	4SEL						_
		CUST	OMER D	RAWING	N	10D N°	
ninium Plug 8D series							
ir	NPRDS / PROJECT 859						4
This document is the property of SOURIAU							1
.CON	VI	it must not be reproduced or communicated without permission					
U DRG N°						SHEET	
N04	SEL-C			A		2/2	J
	D		I	А			