

TYPE QDA
QIKLUG™ Terminal



Heavy-duty terminal for a wide range of cable to equipment studs. One-hole tongue finished on both sides.

Catalog Number	Conductor Range	Stud Size
QDA8C	14 sol. - 8 str.	3/8
QDA4C	8 - 4 str.	3/8
QDA1C	4 - 1 str.	3/8
QDA26	1/0 - 2/0 str.	1/2
QDA28	3/0 - 4/0 str.	1/2
QDA31	250 - 500 kcmil	5/8
QDA34	400 - 500 kcmil	3/4
QDA40	600 - 800 kcmil	1

TYPES Q2A-2, Q2A-2N, Q2A-4N
QIKLUG™ Terminal



Heavy-duty terminal for a wide range of copper cable. Joins two cables to equipment pads or bars. Two hole and four hole tongue.

Catalog Number	Conductor Range	Stud Hole Size	Stud Hole Centers
Q2A1C-2	4 - 1 str.	3/8	1
Q2A26-2N	1/0 - 2/0 str.	1/2	1-3/4
Q2A28-2N	3/0 - 4/0 str.		
Q2A31-2N	250 - 350 kcmil		
Q2A34-2N	400 - 500 kcmil		
Q2A40-2N	600 - 800 kcmil		
Q2A28-4N	3/0 - 4/0 str.		
Q2A31-4N	250 - 350 kcmil		
Q2A34-4N	400 - 500 kcmil		
Q2A40-4N	600 - 800 kcmil		
Q2A44-4N	850 - 1000 kcmil		
Q2A46-4N	1100 - 1500 kcmil		

TYPES Q3A-2N, Q3A-4N
QIKLUG™ Terminal



Heavy-duty terminal for a wide range of copper cable. Joins three cables to equipment pads or bars.

Catalog Number	Conductor Range	Stud Hole Size	Stud Hole Centers
Q3A28-2N	3/0 - 4/0 str.	1/2	1-3/4
Q3A31-2N	250 - 350 kcmil		
Q3A34-2N	400 - 500 kcmil		
Q3A28-4N	3/0 - 4/0 str.		
Q3A31-4N	250 - 350 kcmil		
Q3A34-4N	400 - 500 kcmil		
Q3A40-4N	600 - 800 kcmil		
Q3A44-4N	850 - 1000 kcmil		
Q3A46-4N	1100 - 1500 kcmil		
Q3A48-4N	1600 - 2000 kcmil		

TYPE KA-U
Universal Terminal
(1 Conductor)
For Aluminum and Copper Conductors




Fig. 1

Fig. 2



These dual-rated one conductor lugs are constructed from high strength aluminum alloy and electro tin-plated to provide low contact resistance.

Catalog Number	Conductor Range	Figure Number	Recommended Tightening Torque (in-lb) ▲
KA6U	14 - 6 str.	1	45
KA2U	14 - 2 str.	1	50
KA25U	14 - 1/0 str.	1	50
KA26U	6 - 2/0 str.	1	120
KA29U	6 str. - 250 kcmil	2	275
KA30U	6 str. - 300 kcmil	2	275
KA31U	6 str. - 350 kcmil	2	275
KA34U	4 str. - 500 kcmil	2	500
KA36U	2 str. - 600 kcmil	2	500
KA40U	300 - 800 kcmil	2	550
KA44U	500 - 1000 kcmil	2	550

▲ Listed torque values are for maximum conductor size accommodated.

TYPE K2A-U
Universal Terminal
(2 Conductors)
For Aluminum and Copper Conductors




Fig. 1

Fig. 2



Compact, wide-range, tin-plated aluminum terminal for use with two copper or aluminum cables.

Catalog Number	Conductor Range	Stud Hole Size	Stud Hole Spacing	Fig. No.	Recommended Tightening Torque (in-lb) ▲
K2A25U	Two: 14 - 1/0 str.	1/4	—	1	50
K2A26U	Two: 14 - 2/0 str.	1/4	—	1	120
K2A29U	Two: 6 str. - 250 kcmil	3/8	—	2	275
K2A31U	Two: 4 str. - 350 kcmil	1/2	—	2	275
K2A36U	Two: 2 str. - 600 kcmil	1/2	—	2	375
K2A40U	Two: 300 - 800 kcmil	5/8	—	2	550
K2A44U	Two: 500 - 1000 kcmil	5/8	—	2	550
K2A31U-2N*	Two: 6 str. - 350 kcmil	1/2	1-3/4	3	275
K2A36U-2N*	Two: 2 str. - 600 kcmil	1/2	1-3/4	3	375
K2A40U-2N*	Two: 300 - 800 kcmil	1/2	1-3/4	3	375
K2A44U-2N*	Two: 500 - 1000 kcmil	1/2	1-3/4	3	375

* Tongue holes drilled per NEMA standards.

▲ Listed torque values are for maximum conductor size accommodated.