



SSR21NV-M10475

Aliases (UALM21V1047500)

KEMET, SSR21NV-M/NH-M, AC Line Filters, Common Mode, 47.5 mH







Click here for the 3D model.

Dimensions	
L	22mm MAX
т	16mm MAX
Н	27mm MAX
LL	3.5mm +/-0.5mm
S	13mm +/-0.5mm
S1	10mm +/-0.5mm
Wire Size	0.32mm

Packaging Specifications Packaging

Packaging	Tray
Packaging Quantity	450
Component Weight	14.5 g

General Information	
Series	SSR21NV-M/NH-M
Style	Through-Hole
Features	High Performance, High Impedance, Strong Inductance
RoHS	Yes
Miscellaneous	65 (K) Temperature Rise Max.
Core	Mn-Zn Ferrite

Specifications	
Voltage AC	250 VAC
Inductance	47.5 mH (10 kHz)
Current	1A
Temperature Range	-25/+120°C
DC Resistance	580 mOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.