


Model 5952A Adjustable Tip Test Probe Set



FEATURES

- Slim retractable probe fully insulated to within 1/8" (3,18) of tip
- Needle point tip adjusts to desired length from 0-3" (0-76mm)
- Stainless Steel needle point easily pierces varnish and thin insulation
- Tip can be re-pointed if necessary
- Multi-stacking Banana plug molded directly on the wire
- Banana plug spring is nickel plated Beryllium Copper for long insertion life
- 4 foot test lead wire is silicone insulated for high temperature resistance and flexibility at low temperature.
- Wear indication with double insulated (dual extruded) silicone leads shows black inner layer for increased safety.

MATERIALS

Probe Body: Polypropylene and PVC, color: one black, one red.

Tip: Stainless Steel

Wire: 20 AWG, Silicone insulation

RATINGS:

Operating Voltage: 30 Vrms/42.4 Vpk/60 Vdc

Current: 3 Amperes

ORDERING INFORMATION

Model 5952A

Includes a set of one black and one red test lead

USA: Sales: 800-490-2361
Technical Support: technicalsupport@pomonatest.com
Fax: 425-446-5844

Europe: 31-(0) 40 2675 150 **International:** 425-446-5500

Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): .xx = ± 0.02 " (.51 mm), .xxx = ± 0.005 " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.