

6 5 4 3 2 1

APPROVED: \_\_\_\_\_  
 DATE: \_\_\_\_\_ TITLE: \_\_\_\_\_

Rev	AWO #	Description	Date	Appr
-		RELEASED	11/12/20	
A		UPDATE DRAWING	4/7/21	LH/RC

RECOMMENDED PCB LAYOUT

**SPECIFICATIONS:**

Material:  
 Insulator: PA66, rated UL 94V-0  
 Insulator color: Green  
 Screw: M2.5  
 Contact: Copper Alloy, Tin plated.  
 Electrical:  
 Voltage rating: 300 VAC  
 Current rating: 12 Amp  
 Dielectric withstanding voltage: 1,600 VAC for 1 minut  
 Mechanical:  
 Torque: 0.4Nm  
 Wire Range: 26-14 AWG  
 Wire strip length: 5~6mm  
 Environmental:  
 Operating temperature: -40°C to +105°C  
 Environmental:  
 Lead free, RoHS compliant.

Poles: 2 thru 24  
 A = .200 [5.08] X No. of Positions  
 B = .200 [5.08] x No. of Spaces

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED			909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710	
INCHES	HOLES			
.X ± .10	∅X ± .10			
.XX ± .020	∅XX ± .015			
.XXX ± .015	∅XXX ± .010			
DRAWN	LH	11/12/20	TITLE	
CHECKED	RC	11/12/20	EURO BLOCK, .200 [5.08] PITCH, 45 DEGREE ANGLE	
APPROVED			SIZE	PART NO.
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY AND SHOULD NOT BE USED WITHOUT PRIOR WRITTEN PERMISSION FROM ADAM TECH			X	EB21A-XX-D-DA
			REV. A	
REF: S00067C	SCALE: NTS	SHEET 1 OF 1		

6 5 4 3 2 1