


TOLERANCE UNLESS OTHERWISE SPECIFIED				
.X	±0.25			
.XX	±0.13			
.XXX	±0.05			

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL



NOTES:

MATERIAL:

**HOUSING:** THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, TIN PLATED

CONTACT: COPPER ALLOY, GOLD FLASH PLATED

**OPERATING TEMPERATURE:** -55°C ~ 125°C

POWER/CO-AX CONTACT RATING: 20A (CURRENT)

(IF PRESENT)


SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT


SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.

**INSULATOR RESISTANCE:** 5000MΩ min.

**DIELECTRIC** 

WITHSTANDING VOLTAGE: 1000V AC rms





## **COMBINATION D-SUB**



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

SW REFERENCE NO.: 630 C	OMBO ASSEMBLY				
DRAWN: C.B	DATE: JAN. 01/2019				
CHECKED:	DATE:				
SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 2				
DRAWING NUMBER: 630-21W	1240-2T1 ISSUE				

630-21W1240-2T1

PART NUMBER:



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY. TOLERANCE UNLESS OTHERWISE SPECIFIED

.X ±0.25 .XX ±0.13 .XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING
DO NOT MAKE MANUAL REVISIONS TO MASTER.



ORIGINAL (1)

2W2





5W1

0000 3W3








11W1

○ ○ ○ ○ ○ ○ ○ ○ ○





13W3









17W5





13W6





21W4









## **COMBINATION D-SUB**



	DRAWN: C.B		DATE: JAN. 01/2019			
	CHECKED:		DATE:			
;	SCALE: N.T.S		SHEET	2	OF	2
)	DRAWING NUMBER:	630-21W1240-2T1		ISSUE		
3	PART NUMBER:	630-21W	1240-2T	1		1

630 COMBO ASSEMBLY

SW REFERENCE NO .: