© Copy	rial Composition yright 2005. IPC, Ban tional and Pan-Ameri	nockburn, Illinois. A	Il rights reserved un ntions.	nder both	This docume level parts, th	ent is a declar he declaration	ration of t n encomp	the substances basses all low	s within the er level mat	manufactur erials for w	rer listed it hich the m	em. Note anufactu	e: if the item is an irer has engineerir	assembly with low g responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form T   http://www.ipc.org/IPC-175x Distribution				e *	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfg Information				
Supplier Information															
Company name*	Company un	Company unique ID			Unique ID Authority					Response Date*					
nsemi											2023-06-08				
Contact Name	Title - Conta	Title - Contact			Phone - Contact*					Email - Contact*					
Product-Env-Stewards	Product Envi	Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com						
uthorized Representative*	Title - Repre	Title - Representative			Phone - Representative*				Email - Representative*						
Product-Env-Stewards	Product Envi	Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com						
Requester Item Nu	NCP152MX280180TC Dual 150		m Number Mfr Item Name			Effective Da	ate Ver	sion	Manufacturing Site		V	Veight*	UOM	Unit Type	
			Dual 150 mA, Lov Voltage Regulator			2023-06-08			MY1		1	.87	mg	Each	
Manufacturing Procces	s Information														
Terminal Plating / C	Grid Array Material	Terminal Base	Alloy J	J-STD-020 MSL Rating		Peak Process Body Tempera		dy Temperati	ture Max Time at Peak Temp		Temperatu	ire Nu	mber of Reflow C	ycles	
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		no CU Alloy	CU Alloy 1			260		C	30		second	ls 3			
Comments															
evel 1 - maximum time at pe	ak temperature duri	ng soldering is 10-3	0 seconds												
or more information regard	ling material compos	sition please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU												
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all							
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	0.09	mg	Supplier	Silicon (Si)	7440-21-3		0.09	mg	
Die Attach	0.03	mg	Supplier	Silver (Ag)	7440-22-4		0.0225	mg	
			Supplier	Epoxy resins	129915-35-1		0.0075	mg	
Lead Frame	0.82	mg	Supplier	Silver (Ag)	7440-22-4		0.0328	mg	
			Supplier	Tin (Sn)	7440-31-5		0.0021	mg	
			Supplier	Zinc (Zn)	7440-66-6		0.0018	mg	
			Supplier	Chromium (Cr)	7440-47-3		0.0021	mg	
			Supplier	Copper (Cu)	7440-50-8		0.7813	mg	
Mold Compound-Black	0.88	mg		Epoxy resin	proprietary data		0.0616	mg	
			Supplier	Phenolic Resin	Proprietary Data		0.0616	mg	
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.132	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.0044	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		0.6204	mg	
Plating	0.02	mg	Supplier	Tin (Sn)	7440-31-5		0.02	mg	
Wire Bond - Au	0.03	mg	Supplier	Gold (Au)	7440-57-5		0.03	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).