


## C052H103K1G5GA7061

RAD-LDD Indust COG HT200C, Ceramic, 0.01 uF, 10%, 100 VDC, COG, High Temp, 200C, Radial Molded, Gold Termination, Industrial Grade, Lead Spacing = 5.08mm



Click here for the 3D model.

Dimensions	
L	4.83mm +/-0.25mm
Н	5.97mm +/-0.25mm
Т	2.29mm +/-0.25mm
S	5.08mm +/-0.38mm
LL	31.75mm MIN
F	0.635mm +0.102/-0.051mm
G	1.14mm MAX
K	4.83mm +/-0.25mm

Packaging Specifications			
Packaging	Tray		
Packaging Quantity	50		

General Information	
Series	RAD-LDD Indust COG HT200C
Style	Radial
Description	High Temp, 200C, Radial Molded, Gold Termination, Industrial Grade
Features	Commercial
RoHS	With Exemptions
REACH	SVHC (Pb - CAS 7439-92-1)
SCIP Number	e1a5b9fc-0de5-4ce0-a6ef-55df071d82eb
Termination	Gold
AEC-Q200	No
Halogen Free	Yes
Component Weight	493 mg

Specifications				
Capacitance	0.01 uF			
Capacitance Tolerance	10%			
Voltage DC	100 VDC			
Dielectric Withstanding Voltage	250 VDC			
Temperature Range	-55/+200°C			
Temperature Coefficient	COG			
Dissipation Factor	2.5%			
Aging Rate	0% Loss/Decade Hour			
Insulation Resistance	100 GOhms			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.