


C931U561KWYDBAWL40

Not for New Design

C900AS SFTY X1-760 Y1-500, Ceramic, 560 pF, 10%, 760 VAC (X1), 500 VAC (Y1), Y5P, Lead Spacing = 10mm



General Information Series C900AS SFTY X1-760 Y1-500 Style Radial Disc RoHS Yes Termination Tin Failure Rate N/A Qualifications UL, ENEC, VDE, CSA, CAN AEC-Q200 No Halogen Free Yes

Specifications	
Capacitance	560 pF
Capacitance Tolerance	10%
Voltage AC	760 VAC (X1), 500 VAC (Y1)
Dielectric Withstanding Voltage	4000 VDC
Temperature Range	-40/+125°C
Temperature Coefficient	Y5P
Dissipation Factor	2.5%
Insulation Resistance	10 GOhms
Safety Class	X1/Y1

Click here for the 3D model.

Dimensions	,
D	10mm MAX
т	7mm MAX
S	10mm +/-1mm
LL	4mm +/-1mm
F	0.55mm +/-0.1mm

Packaging Specifications

Packaging	Bulk, Bag
Packaging Quantity	500

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.