

## R413W3680JB00M

Aliases (413W3680JB00M)

R41, Film, Metallized Polypropylene, Safety, 0.68 uF, 20%, 300 VAC (Y2), 1000 VDC, 110 °C, Lead Spacing = 37.5mm



Click here for the 3D model.

Dimensions	,
L	41.5mm +0.3/-0.7mm
Н	28.5mm +0.1/-0.7mm
Т	16mm +0.2/-0.7mm
S	37.5mm +/-0.4mm
LL	3.5mm +0.5mm
F	1mm +/-0.05mm

Packaging Specifications	
Packaging	Tray
Packaging Quantity	216

General Information	
Series	R41
Dielectric	Metallized Polypropylene
Style	Radial
Features	EMI Safety
RoHS	Yes
Lead	Cut
Safety Class	Y2
Qualifications	ENEC, UL, cUL, CQC
AEC-Q200	No
THB Performance	No
Component Weight	22.71 g

Specifications				
Capacitance	0.68 uF			
Capacitance Tolerance	20%			
Voltage AC	300 VAC (Y2)			
Voltage DC	1000 VDC			
Temperature Range	-40/+110°C			
Rated Temperature	110°C			
Dissipation Factor	0.2% 1kHz			
Insulation Resistance	44.118 GOhms			
Max dV/dt	300 V/us			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.