



- NOTES:
1. MOUNTING HARDWARE SHIPPED UNASSEMBLED.
 2. RATED 15 AMP, 24 VOLT DC AT 105° C (CURRENT CARRY ONLY) WHEN USING 14 AWG STRANDED CONDUCTOR CABLE.
 3. IP68 RATED WHEN MATED TO S15KS SERIES PLUGS.
 4. THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					FINISH			MATERIAL	
					SPEC No.			SPEC No.	
					FIRST USED ON		SCALE 1.5:1		
					DATE DRAWN	BY	CHKD	APVD	
					5-10-19	SRC	SRC	TJK	
							6-29-22	7/25/22	
					NAME			PART No.	
					15 AMP JACK ASSEMBLY. RoHS			ST15S	
					DO NOT SCALE DRAWING			REV	
								A	
A	28515	7/18/22	TJK	TJK					
REV	ECO NUMBER	DATE	BY	APVD					
REVISIONS									