



Product: 5120FL

Fire Alarm, #14-2c BC, Shielded, FPLR

Product Description

Fire Alarm Cable, Riser-FPLR, 2-14 AWG solid bare copper conductors with polypropylene insulation, overall Beldfoil® shield, PVC jacket with ripcord

Technical Specifications

Product Overview

Suitable Applications:	Fire Alarm, Monitor/Detection	on, Circuits: Audio, C	Control, Initiating,	Notification, Noisy Environm	ent
Construction Details					
Conductor					
	A Circo Chronding	Medavial			
Element Number of Elemen Conductor(s) 2		Material			
		- Bare Copper			
Insulation					
Element Material	Nom. Thickness Nom.	Insulation Diameter	r Color Code		
Conductor(s) PP - Polypropylene	0.010 in (0.25 mm) 0.845 i	in (21.5 mm)	Black, Red		
Outer Shield					
Shield Type Material	Coverage Drainwi	ге Туре			
Tape Bi-Laminate (Alum+	Poly) 100% 22 AWG ((Solid) TC			
Outer Jacket					
	hickness Nom. Diamete	r Ripcord			
PVC - Polyvinyl Chloride 0.017 in					
Overall Cable Diameter (Nominal): 0.209 in (5.31 mm)					
Electrical Characteristics					
Electricals					
Element Nom. Conductor D	OCR Nom. Capacitance Co	nd-to-Cond Nom.	Capacitance Co	nd-to-Other (Conds + Shie	d) Max. Current
Conductor(s) 2.43 Ohm/1000ft	60 pF/ft (200 pF/m)	108 pl	F/ft (354 pF/m)		25 Amps per conductor @ 30°C
Voltage					
UL Voltage Rating					
300 V (FPLR)					
Mechanical Characteristic	cs				
Temperature					
UL Temperature Operating	0				
75°C -20°C to +75°C	1				
Bend Radius					
Stationary Min. Installation	n Min.				
3.075 in (78.11 mm) 3.075 in (78.					
Max. Pull Tension: 206.6 lbs (93.71 kg)					
	· · · · · · · · · · · · · · · · · · ·				

Bulk Cable Weight:

36 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Reaction to Fire:	UL 1666 Riser, IEEE 1202 FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 760, FPLR
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	California State Fire Marshall
Plenum Number:	6120FL

History

Update and Revision: Revision Number: 0.447 Revision Date: 01-20-2023

Part Numbers

Variants

ltem #	Color	UPC
5120FL D151000	Blue	612825156918
5120FL 0021000	Red	612825156925

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.